

A Combination of Local Approaches for Hierarchical Music Genre Classification



Antonio R. S. PARMEZAN¹, Diego Furtado SILVA², Gustavo E. A. P. A. BATISTA³

¹Institute of Mathematics and Computer Science – University of São Paulo, São Carlos, Brazil


²Department of Computing – Federal University of São Carlos, São Carlos, Brazil

³School of Computer Science and Engineering – University of New South Wales, Sydney, Australia



Introduction


- Music genre is an essential metadata
- Classifying music genres is a challenging task
- Music genres typically respect a hierarchical structure




Major Contributions

- We combine the per node and per parent node hierarchical classification approaches
- Our approach is more robust and faithful to the music genre classification scenario
- We advocate using decision trees as base-level classifiers

Experimental Evaluation




Proposed Approach



 Multiclass classifiers
 Binary classifiers

Examples	Attributes					Class (Y)
	X_1	X_2	X_3	...	X_M	
E_1	X_{11}	X_{12}	X_{13}	...	X_{1M}	$L \rightarrow L.1 \rightarrow L.1.1$
E_2	X_{21}	X_{22}	X_{23}	...	X_{2M}	$L \rightarrow L.1 \rightarrow L.1.2$
E_3	X_{31}	X_{32}	X_{33}	...	X_{3M}	$L \rightarrow L.2 \rightarrow L.2.2$
\vdots	\vdots	\vdots	\vdots	\ddots	\vdots	\vdots
E_N	X_{N1}	X_{N2}	X_{N3}	...	X_{NM}	$L \rightarrow L.1 \rightarrow L.1.1$



Hypothetical class hierarchy

Results Overview

Evaluation measure	Hierarchical approaches			
	FC	LCN	LCL	Hybrid
hP(%)	67.62	72.36	69.86	75.79
hR(%)	66.10	71.96	69.46	77.38
hF(%)	66.88	72.16	69.66	76.57
Runtime	48 min	92.44 h	4.41 h	3.53 h

Conclusion

- Our results showed that the designed approach is better than the traditional ones
- The hierarchical performance measures were not very high due to the tough nature of the problem. In other words, it is not easy to classify among 120 genres